


All heater settings are managed by wiring connections of our single multi-tap heater coil Model # DH18-37-50												
CheapHeat™ Heater Output Electric vs Propane mbtu		Minimum 30 Amp Shore Power		Minimum 50 Ar	mp Shore Power	Minimum 50 Amp Shore Power						
		DH18 Setting		DH37 Setting		DH50 Setting						
SUBURBAN MODELS			Plenum Sys. (3) 4x8 Register Min		Plenum Sys. (4) 4x8 Register Min	Ducted System ***(6) 4" Run Min						
DH18	SF Series-20 mbtu	YES	YES									
	SF Series 25 mbtu	YES	YES									
DH37	SF Series 30 mbtu			YES	YES							
DH 37 or DH50	SF or SH Series 35 mbtu			YES	YES	YES	YES					
DH50 Setting	SF or SH Series 42 mbtu					YES	YES					
DH50	SH Series 25/42 mbtu			YES	YES	YES	YES					
ATWOOD HYDRO FLAME MODELS AFMD, AFLD, 8500, 8900		Ducted System **(3) 4" Run Min	Plenum Sys. (3) 4x8 Register Min	Ducted System **(5) 4" Run Min	Plenum Sys. (4) 4x8 Register Min	Ducted System ***(6) 4" Run Min	Plenum Sys. (5) 4x8 Register Min					
DH18	Atwood 20 mbtu	YES	YES									
DH18	Atwood 25 mbtu	YES	YES									
DH37	Atwood 30 mbtu			YES	YES							
DH37 or DH50	Atwood 35 mbtu			YES	YES	YES	YES					
DH50	Atwood 40 mbtu					YES	YES					

^{*}Note: Surburban 2-Stage furnaces requires special Change-over switch (Call Ph# 425-408-3140)

***** NOTE: Vertical installed Furnaces require that our DH18-37-50 Heater Coil be upgraged with a 200 F degree TOD (Call Ph# 425-408-3140)



- * With the Ducted
 Add-on system (4 inch
 ducts) all ducts need to
 be moved to the end of
 the new cabinet
 adapter (No
 Exceptions) MAKE
 SURE YOU HAVE THAT
 ADDITIONAL ROOM.
- ** The CheapHeat™ Hybrid Kit work on vertically installed and also requires L200 TOD from upgrade (contact RV Comfort Systems.

FURNACE BRAND			CLEARANCE MEASUREMENT				
			Α	В	С	D	
Atwood	AFMD	SAH7 & SAV-7	0	2.5"	1 3/4	5.75"	
Atwood	AFMD	PAH-7 & PAV-7	1"	0.5"	1.75	6"	
Atwood	AFLD	SAH-9 & SAV-9	0	1.5"	1.75	5.75"	
Atwood	AFLD	PAH-9 & PAV-9	1"	0.5"	1.75	6"	
*Atwood	**8500	AT10	0	3"	1.25"	5"	
*Atwood	**8900	SAH-89	0	1"	1.75"	5.75"	
Atwood	8900	PAH-89	1"	0.5	1.75"	6"	
Suburban	SF	SFH-7 & SFV-7	0	2.5"	0	5.75"	
Suburban	SF	PFH-7 & PFV-7	1"	0.5"	0	6"	
Suburban	SH	SHH-9 & SHV-9	0	1.5"	0	5.75"	
Suburban	SH	PHH-9 & PHV-9	1"	0.5"	0	6"	
Suburban	SF	DRV	0	0.5"	0.5"	8"	

^{**}Note: Atwood Hydro Flame 2-Stage furnace WILL NOT work with this system:

^{***} Note: These 4 inch duct runs are individual ducts originating at the furnace and 2 inch duct runs do not count

^{****} Note: In most cases the 6th duct run will have to be added and it is suggested that it be an open duct running in the basement towards the back of the coach extending back 6 to 8 feet.